

"Australia's Only
Genuine Wholesaler"

Size/ Part No.	Shore Hardness	Type	Max Compressive Load(kg)	STATIC DEFL(mm)	Thread Size	Bolt/Nut
F 13x13	A	1	4.5	1	3/16"BSW x13L	3/16"BSW x4Deep
F 16x15	A	1	4.1	1	M5x0.8P x12L	M5x0.8P x5 Deep
		2	4.3	1		
		3	4.5	1		
F 19x19	A	1	17	3	1/4"BSW x19L	1/4"BSW x6 Deep
	B	2	28	3		
F 20x20	C	1	55	4	M5x0.8P x12L	M5x0.8P x5 Deep
		2	57.5	4		
		3	57.5	4		
F 20x25	A	1	9.8	3	M6x1P x17L	M6x1P x6 Deep
	B	2	18	3		
	C	3	30	3		
F 25x20	A	1	33.8	3.5	M6x1P x13L	M6x1P x6 Deep
	B	2	55	3.5		
	C	3	80	3.5		
F 25x30	A	1	13.8	3	M8x1.25P x20L	M8x1.25P x6 Deep
	B	2	23	3		
	C	3	32	3		
F 30x22	A	1	46	3.5	M8x1.25P x25L	M8x1.25P x6 Deep
		2	52	3.5		
F 30x30	A	1	21	3	M8x1.25P x21L	M8x1.25P x6 Deep
		2	23	3		
		3	23	3		
F 35x25	A	1	15	1.5	3/8"BSW x38L	3/8"BSW x6 Deep
	B	2	27	1.5		
	C		51	1.5		
F 38x25	A	1	65	4	M8x1.25P x17L	M8x1.25P x6 Deep
	B	2	127	4		
	C	3	165	4		
F 38x38	A	1	61	6	M8x1.25P x17L	M8x1.25P x10 Deep
	B		78	6		
	C		100	6		
F 40x30	B	1	108	5	M8x1.25P x25L	M8x1.25P x6 Deep
		2	113	5		
		3	118	5		
F 40x40	A	1	65	6	M10x1.5P x38L	M10x1.5P x10 Deep
	B	2	93	6		
	C	3	132	6		
F 50x40	A	1	83	5	M10x1.5P x22L	M10x1.5P x12 Deep
	B	2	149	5		
	C		204	5		

Size/ Part No.	Shore Hardness	Type	Max Compressive Load(kg)	STATIC DEFL(mm)	Thread Size	Bolt/Nut
F 50x45	B	1	151	7	M10x1.5P x25L	M10x1.5P x12 Deep
F 50x50	A	1	71.5	7	M10x1.5P x22L	M10x1.5P x12 Deep
	B	2	132	7		
	C	3	202	7		
F 55x38	A	1	55	3	3/8"BSW x34L	3/8"BSW x10 Deep
	B	2	89	3		
	C		122	3		
F 60x50	A	1	112	6.5	M12x 1.75P x27L	M12x 1.75P x15 Deep
	B	2	201	6.5		
	C	3	285	6.5		
F 75x55	A	1	178	6	M12x 1.75P x37L	M12x 1.75P x15 Deep
	B	2	292	6		
	C	3	443	6		
F 80x60	A	1	230	8	M12x 1.75P x30L	M12x 1.75P x20 Deep
	B	2	352	8		
	C	3	505	8		
F 100x 55	A	1	324	6	M16x2P x43L	M16x2P x20 Deep
		2	580	6		
		3	818	6		

Shore Hardness	
A	40.50
B	55.65
C	65.75

Method of Ordering				
F	25	30	A	2
F	D	T	Shore Hardness	Type

